

APP CRS	Rwy Ldg	8394
276°	TDZE	7
	Apt Elev	65

RNAV (RNP) Z RWY 28R

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)

RNP AR APCH - GPS. RADAR required.

Simultaneous approach authorized. For uncompensated Baro-VNAV systems, procedure NA below 7°C or above 54°C. For inop ALS, increase RNP 0.15 visibility to RVR 5500 and increase RNP 0.30 visibility to 1¾ SM.

MALSR

AS

MISSED APPROACH: Climb to 800 then climbing right turn to 4000 direct HUKUK and hold, continue climb-in-hold to 4000.

D-ATIS 135.0	MIAMI APP CON 133.775 285.6	FORT LAUDERDALE TOWER 119.3 257.8	GND CON 121.4
-----------------	--------------------------------	--------------------------------------	------------------

MISSED APCH FIX  
4 NM  
307°  
127°  
HUKUK

Diagram illustrating the RNAV (RNP) Z RWY 28R approach. Key waypoints and altitudes include: JENPO (5000, 210K), CUSRA, PRHIB (2000, 1.7), FUZZY (2000, 276°, 6.3), and HUKUK (4000, 210K). The approach path is defined by a series of turns and altitudes: 4000 096° (3.2) to CUSRA, 2500 153° to PRHIB, 2500 233° (15.6) to FUZZY, and 4000 290° (9.2) to HUKUK. The final approach segment is 276° (6.1) to RWY 28R. A missed approach procedure is shown starting from HUKUK, climbing to 800, then turning right to 4000 and holding.

ELEV 65 TDZE 7

800 4000 HUKUK

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).

See planview for multiple IF locations.

276°

Diagram showing the approach path from RWY 28R to SNAPE (2000) and HUKUK (4000). The path is defined by a series of turns and altitudes: 276° (6.1) to RWY 28R, 276° (6.1) to SNAPE, and 276° (6.1) to HUKUK. The final approach segment is 276° (6.1) to RWY 28R.

GP 3.00° TCH 49

CATEGORY	A	B	C	D
RNP 0.15 DA		362/40	355 (300-¾)	
RNP 0.30 DA		618-1⅜	611 (600-1⅜)	

HIRL Rwy 10L-28R and 10R-28L

AUTHORIZATION REQUIRED

FORT LAUDERDALE, FLORIDA  
Amdt 2 12AUG21

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)  
26°04'N-80°09'W

RNAV (RNP) Z RWY 28R